

CET**CLIFF TAIWAN**

sales@cliffuk.co.uk

SPEAKER SPECIFICATION

No: 93112204 Model FC68181

1	MODEL	TMP-040CN(F40P03B)
2	Dimension	Outer Diameter 40 mm Baffle Opening 37.0 mm.
		Height Refer to drawing Weight 5.0 Gram.
3	Magnet	Materials Rare Earth Size $\phi 12.5 \times 1.7$ mm.
4	Nominal Impedance	8 Ohm $\pm 15\%$ At 1000 Hz
5	Power Rating	Normal 0.2 W. Maximum 0.4 W.
6	Lowest Resonant Frequency	300 \pm 60 Hz
7	Output Sound Pressure Level (S.P.L.)	82 \pm 3 db / 1 Watt 1 Meter.
		Average at 400,500,600,800 HZ
8	Frequency Range	160~20K Hz. Average SPL-10 db.
9	Distortion	5 % Maximum At 1000 Hz 0.2 W.
10	Abnormal Sound Test.	Must be Normally Tested By 1.26 Volts Sine Wave.
11	Load Test	White Noise with Weighted Filter 1.26 Volts. (RMS) 24 Hrs.
12	Operation Temperature	-25°C ~ +60°C 16 Hours.
13	Storage Temperature	-40°C ~ +70°C 2 Hours.
14	Polarity	Diaphragm shall move Forward when Apply a Positive DC
		Current to the "+" or "Marked" Terminal.
15	Remarks	Above specifications on the strength of CNS4784 and CNS4785.

